

MATS-2010SD

Soft Magnetic Material Dynamic Hyteresisgraph System

Model MATS-2010SD



Automatic measurement on basic magnetization curve and magnetic hysteresis loop under static state of soft magnetic material, accurate measurement on static magnetic characteristic parameters such as initial permeability μ_i , maximum permeability μ_m , saturation magnetic induction B_s , remanence B_r , coercive H_c and hysteresis losses P_u .

Windows measurement software applied simply. It conforms to China National Standards GB3657 - 83, industry standard SJ / T10281 - 91 and international standard IEC60404 - 4.

In accordance with measuring principle of ballistic method, combine computer control technology, A/D and D/A, replace conventional ballistic galvanometer with electronic integrator, realize analog ballistic method measurement under microcomputer control, can completely eliminate non-instant error caused by ballistic galvanometer in classical ballistic method, with high measurement accuracy, fast speed and good repeatability, can eliminate the influence of various artificial factors, and supply reliable basis for research on material magnetization process.


General Features

Software Features

Software Screen

Technical Data

Standard Package



©Copy Right 2001 YUXIANG All Rights Reserved
 Add :F/16, Jinyuan plaza, # 57 South Hubin.Road, Xiamen, CHINA 361004
 Tel : (86)592 2295387 (86)592 2217138 Fax: (86)592 2207122
 Email : yingli@magnets.com.cn