

The Special Magnetizing Power

EX Magnetizing Power



Uses of the special magnetizing power

- **Type of 1504,1506**

magnetizing for micromotor in either inner or outer ways. The magnetized motors' distributions of magnet fields will be in highly uniformity.
- **Type of 1510-20 II,2510-2510-30II**

Magnetizing for multi-pole of teeny pole distance rare earth, one equipment may match with two yokes or two coils
- **Type of 1520-30 II V**

polar-anisotropic and tropism magnet automatically can be loacted the right magnetizing position according to the polarizing axis of the magnets.
- **Type of 4030-30 II**

two work-position uses jointly one magnetizer, magnetizing independently with different voltage.

EX I

EX II

EX III

EX IV

| Model | EX-1504-10 | EX-1506-10 | EX-1510-20 II | EX-1520-30 IIV | EX-2510-30 II | EX-4030-30 II |
|-----------------------------------|--------------------|------------|-----------------------|--------------------------|--------------------------|-----------------------|
| Input Power | AC220V 50~60Hz 10A | | AC220V 50~60Hz 15A | AC220V 50~60Hz 30A | AC220V 50~60Hz 40A | AC220V 50~60Hz 60A |
| Max Output Curent | 10,000 | 10,000 | 20,000×2 | 30,000×2 | 30,000×2 | 30,000×2 |
| Charge Voltage | DC50~1500V | | DC50~1500V | DC50~1500V | DC50~2500V | DC50~4000V |
| Repet Precision Of Charge Voltage | +/- 1V+1 digit | | +/- 1V+1 digit | +/- 1V+1 digit | | |
| Charge Time | 2 sec | | 4 sec | 5 sec | 4 sec | 12 sec |
| The capacity of Condenser | 400 uF | 600 uF | 1000 uF | 2000 uF | 1000 uF | 3000 uF |

| | | | | | | |
|----------------------------|----------------|-----------------|-----------------|-----------------|-------|-------------------|
| The Capacity Of Changing | none | 400/600 | none | 1000/2000 | none | 1000/2000/3000 |
| Main Switch | SCR | | SCR | SCR | | |
| Compare Function | Have | | Have | Have | | |
| Interior Discharge Circuit | Have | | Have | Have | | |
| Enclosure Dimensions | 450W×850D×565H | 450W×1000D×565H | 500W×1000D×900H | 600W×900D×1350H | | 1000W×1000D×2000H |
| Weight | 154Kg | 150Kg | 200Kg | 280Kg | 320Kg | 1200Kg |

©Copy Right 2001 YUXIANG All Rights Reserved

Add :F/16, Jinyuan plaza, # 57 South Hubin.Road, Xiamen, CHINA 361004

Tel : (86)592 2295387 (86)592 2217138 Fax: (86)592 2207122

Email : yingli@magnets.com.cn